

CreteSeal 5500

TECHNICAL INFORMATION

DESCRIPTION CreteSeal 5500 is a specially formulated solvent acrylic lacquer designed to meet the application demands of the decorative concrete finishing industry where very high gloss levels are required beyond the levels obtained by standard sealers.

Once cured the film forms a tough protective coating which both protects and highlights the colours in the finish. Formulated specially for the professional contractor.

SUITABILITY CreteSeal 5500 is recommended for use on Imprinted Concrete, Stencil Concrete and Texture Coat surfaces where a thicker layer is required. Also suitable in high traffic areas.

TYPICAL PROPERTIES

Appearance	Thin clear solvent based liquid
Solids content	Approx 25%
Minimum application temperature	10 Degrees C

METHOD OF APPLICATION CreteSeal 5500 is designed to be both spray and broom applied. Best results are obtained by putting down two coats with adequate drying time between. Additionally improved penetration of the first coat can be obtained by the addition of approx. 15-25% Solvent. Improved penetration is desirable as the product is relatively high in both solids and viscosity.

COVERAGE The following coverage rates are approximate and for estimating purposes only. Make test applications on actual surfaces to determine exact coverage rates. Approximately 5-7m²/litre depending on porosity of substrate.

* Rotate stock and protect from freezing

LIMITATIONS Chlorine in some Pool Systems may reduce the life of the sealer.

* Not recommended for use on gradients greater than 1:7.

* Not recommended for interior use.



THE INFORMATION PRESENTED IS BELIEVED TO BE ACCURATE. HOWEVER NO GUARANTEE IS IMPLIED OR GIVEN. USER'S SHOULD CONDUCT THERE OWN TESTING TO DETERMINE THE SUITABILITY OF ANY PRODUCT FOR A PARTICULAR PURPOSE.

Distributed by: **Colourcrete NZ 2012 Ltd**

Unit 2,11 Blackburn Road, East Tamaki Auckland • PO Box 39187, Howick Auckland 2145

FREE PHONE 0508 222 012 • Ph: 09 274 7007 • WWW.COLOURCRETE.CO.NZ